

Bernoulli effect in superconductors and Cooper-pair mass spectroscopy

M.V. Simkin

*Department of Physics, Brown University,
Providence, RI 02912-1843*

Abstract

Recently Mishonov (Phys. Rev. B **50**, 4009 (1994)) suggested to measure the Cooper-pair effective mass using current-induced contact potential difference in superconductors. In this Comment it is shown that actual experiments can be substantially simplified.

74.20.-z, 74.76.-w

In his recent articles Mishonov [1], [2] addressed the intriguing problem of the measurement of the Cooper-pair mass [3]. It worth noting that he not only justified the possibility of this measurement like Greiter *et al* [4] did before him but he also proposed [1] that the Bernoulli effect in superconductors [5] should be such a standard tool for this measurement as the Hall effect is for the measurement of charge carrier density in normal metals. This is a novel point of view as up to now researchers studying the Bernoulli effect [6],[8],[9], [10] where interested only in the effect itself and did not fully realized its value for the material science. In the same article Mishonov [1] suggested several modifications of the experimental methods, used to measure the Bernoulli effect in conventional superconductors [8],[9],[10], which would be more appropriate for layered High-Tc materials. The aim of this Comment is to propose a substantial simplification of these experiments.

In Ref. [1] it was proposed to make a capacitor of superconducting, insulating and normal metal layers (see Fig. 1), to place it in an ac magnetic field B , parallel to these layers and measure the Bernoulli voltage between point contacts (a) and (c). In Ref. [1] it was stated that the contact should be made to the lateral surface of the film, where $B = 0$. It is interesting that in a prototype of this suggested experiment, where a superconducting cylinder was placed in a transverse magnetic field the point contact was indeed made to the place where $B = 0$ (see Fig.1 of Ref.[8]). However in the case of the superconducting film to make such a contact is not only technically complicated, particularly for HTSC films, but also unnecessary. Consider the voltage, as measured by voltmeter, i.e. the electrochemical potential difference, between (a) and (b), V_{ab} , and between (a) and (c), V_{ac} . If $V_{ab} \neq V_{ac}$, then $V_{bc} \neq 0$ i.e. the voltmeter will measure nonzero voltage between two parts of superconductor in contradiction with experiment [7],[8], [9].

Let us now explain where the voltage V_{ab} comes from. When the magnetic field rises from zero to B , Meissner currents build up and the Cooper-pairs at the surface acquire kinetic energy. To make the electrochemical potential uniform the Bernoulli voltage between the surface and the bulk arises. To create this voltage two surface layers of the film become polarized, while electric field outside the superconducting film is zero. This means that the electrochemical potential of the superconducting film changes by the value of kinetic energy of superconducting electrons on the surface of the film. At the same time the electrochemical potential of normal metal plate is unchanged. As a consequence the difference between electrochemical potentials of normal metal and superconducting films is equal to the kinetic energy of the Cooper-pairs at the surface of the superconducting film. This kinetic energy can be expressed in terms of the magnetic field at the surface and Cooper-pairs volume density using London equations. In the case when the film is much thicker than the London penetration depth one easily finds [8],[9] that the difference in electrochemical potentials is:

$$V_{ab} = -\frac{B^2}{8\pi n^* e^*}. \quad (1)$$

Here B is the magnetic field at the film surface, n^* is the Cooper-pairs volume density, $2e^*$ is their charge ($e^* = \pm e$). As was pointed out by Mishonov [1], the sign of the voltage gives us the sign of the charge carriers (Cooper-pairs), and its magnitude gives us their volume density, and, as a consequence, their effective mass m^* (when one knows n^* then m^* can be found from the London penetration depth which depends on m^*/n^*).

Let us now discuss the method of Cooper-pair mass measurement represented in Fig. 1 of Ref. [1]. From the discussion above it is clear that there is no need for the ring electrode, while contact (2) can be made to the superconducting film surface. This means that the layered structure, made by Fiory *et al.* [11], can be used as a magnetic field induced contact potential difference Cooper-pair mass spectrometer even without modification suggested in Ref. [1].

I hope that this Comment may encourage experimentalists to measure the Cooper-pair effective mass using already existing microstructures [11], [12].

I am grateful to A.Houghton, D.I. Khomskii and J.M. Kosterlitz for useful discussions.

References

- [1] T.M. Mishonov, Phys. Rev. B **50**, 4009 (1994).
- [2] T.M. Mishonov, Phys. Rev. B **50**, 4004 (1994).
- [3] M. Tinkham, Introduction to Superconductivity (McGraw-Hill, New-York, 1975) chap. 4.1.
- [4] M. Greiter, F. Wilczek, and E. Witten, Mod. Phys. Lett. B **3**, 9003 (1989).
- [5] F. London, Superfluids (John Wiley and Sons Inc., New-York, 1950), Vol. 1, p. 58, chap. 8.
- [6] A.G. Vijfeiken and F.A. Staas, Phys. Lett. **12**, 175 (1964), E. Jakeman and E.R. Pike, Proc. Phys. Soc. **91**, 422 (1967), G. Rickaizen, J. Phys. C ser. 2 vol. 2, 1174 (1969), K.M. Hong, Phys. Rev. **B12**, 1766 (1975), A.N. Omelyanchuk and S.I. Beloborod'ko, Fiz. Nizk. Temp. **9**, 1105 (1983) [Sov. J. Low Temp. Phys. **9**, 572 (1983)].
- [7] H.W. Lewis, Phys. Rev. **92**, 1149 (1953); **100**, 641 (1955).
- [8] J. Bok and J. Klein, Phys. Rev. Lett. **20**, 660 (1968).
- [9] T.D. Morris and J.B. Brown, Physica **55**, 7609 (1971).
- [10] Yu.N. Chiang and O.G. Shevchenko, Fiz. Nizk. Temp. **12**, 816 (1986) [Sov. J. Low Temp. Phys. **12**, 462 (1986)].
- [11] A.T. Fiory *et al.*, Phys. Rev. Lett. **65** 3441 (1990).
- [12] X.X. Xi *et al.*, Phys. Rev. Lett. **68** 1240 (1992).

Figure 1: Magnetic field induced contact potential difference Cooper-pair mass spectrometer. A capacitor is formed by normal metal (1), insulating (2), and superconducting (3) layers, grown on the substrate (4). This structure is placed in a parallel homogeneous ac magnetic field B . This magnetic field induces the alternating difference (on frequency double to that of magnetic field) in electrochemical potential between the normal metal and superconducting layers given by Eq.1. In the measurement point contact made to the normal plate (a) and to the surface of the superconducting film (b) can be used. Point contact (c) to the side surface of the film is used in discussion only and is not needed in the experiment.

